

Date of receipt: 11/03/21

Date of issue: 14/07/21

Report consists of 5 test reports.

Defects before testing: None

Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

SAMPLE N° 309270

Overall dimensions: 1505 x 560 x 1790 (h) mm

List of test reports:

1. Dimensions EN 1023-1:1996, clause 2.1
2. General safety requirements EN 1023-2:2000 clause 3
3. Stability for non-load bearing screens EN 1023-3:2000, clause. 6.1
4. Stability for load bearing screens EN 1023-3:2000, clause 6.2
5. Dislodgement test for panel mounted components EN 1023-3:2000, par. 6.3
6. Strength test for load bearing office screens EN 1023-3:2000, clause 6.4



This document is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

*The managing director
Dr. Franco Bulian*

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

SAMPLE N° 309270

Date of issue: 14/07/21
Sample weight: Not determined
Sample name: YPSILON CONNECT CON RUOTE



Rear view



Without shelves

TEST REPORT

309270 / 1

Revision: 0
Date of receipt: 11/03/21
Date of test: 27/04/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

Dimensions EN 1023-1:1996, clause 2.1

Configuration type: linear with shelves
Overall dimensions: 1505 x 560 x 1790 (h) mm

Test results:

Height detected:	1790 mm
------------------	---------

Function	Required height mm
Eye contact in a sitting position	≤ 1100
No eye contact in a sitting position	≥ 1400
Eye contact in a upright position	≤ 1400
No eye contact in a upright position	≥ 1800

This test report is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

309270 / 2

Revision: 0
Date of receipt: 11/03/21
Date of test: 29/06/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

General safety requirements EN 1023-2:2000 clause 3

Overall dimensions: 1505 x 560 x 1790 (h) mm

Requirement	Remarks
Accessible corners are rounded with minimum 2 mm radius	≥ 2 mm
The edges of the screen with which the user comes into contact are rounded with minimum 2 mm radius	≥ 2 mm
All other edges are free from burrs and smoothed	Yes
The ends of hollow components are closed or capped	Yes
Movable and adjustable parts are so design that injuries and inadvertent operation are avoided	Yes
The manufacturer shall indicate in his instruction manual how to use the screen in combination with add-on elements	Yes
The manufacturer shall indicate in his instruction manual the admissible load for each type of screen	Yes

This test report is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

309270 / 3

Revision: 0
Date of receipt: 11/03/21
Date of test: 27/04/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

Stability for non-load bearing screens EN 1023-3:2000, clause. 6.1

Type of configuration: linear with shelves
Overall dimensions: 1505 x 560 x 1790 (h) mm

Forward application

Application point: at 1300 mm above the floor

Test results:

Parameter	Requirement	Observed
horizontal displacement 200 mm	does not overturn	does not overturn

Note: measured horizontal overturning force: 87 N

Rearward application

Application point: at 1300 mm above the floor

Test results:

Parameter	Requirement	Observed
horizontal displacement 200 mm	does not overturn	does not overturn

Note: measured horizontal overturning force: 95 N

This test report is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

309270 / 4

Revision: 0
Date of receipt: 11/03/21
Date of test: 04/05/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

Stability for load bearing screens EN 1023-3:2000, clause 6.2

Type of configuration: linear with shelves
Overall dimensions: 1505 x 560 x 1790 (h) mm
Declared load on the product: 20 kg
Declared load on the fixed shelf: 5 kg
Declared load on the hanged shelf: 1 kg

Forward application

Application point: at 1300 mm above the floor on the external vertical upright

Test results:

Parameter	Requirement	Observed
horizontal displacement 200 mm	does not overturn	does not overturn

Note: measured horizontal overturning force: 169,5 N

Reaward application

Application point: at 1300 mm above the floor on the external vertical upright

Test results:

Parameter	Requirement	Observed
horizontal displacement 200 mm	does not overturn	does not overturn

Note: measured horizontal overturning force: 100 N

This test report is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

309270 / 5

Revision: 0
Date of receipt: 11/03/21
Date of test: 04/05/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

Dislodgement test for panel mounted components EN 1023-3:2000, par. 6.3

Type of screen configuration: linear with shelves

Test results:

Screen mounted component: double shelves dim. 1455 x 175 x 12 h mm

Upward force applied:

> 100 N

Remarks: none

Minimum upward force required: 100 N

Screen mounted component: single shelf dim. 1455 x 175 x 12 h mm

Upward force applied:

> 100 N

Remarks: none

Minimum upward force required: 100 N

This test report is part of a PDF file digitally signed by Franco Bulian
on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.

TEST REPORT

309270 / 6

Revision: 0
Date of receipt: 11/03/21
Date of test: 04/05/21
Date of issue: 14/07/21



Sample name: YPSILON CONNECT CON RUOTE

PEDRALI S.P.A.
STRADA PROVINCIALE 122
24050 MORNICO AL SERIO (BG)
ITALIA

Strength test for load bearing office screens EN 1023-3:2000, clause 6.4

Configuration type: linear with shelves
Overall dimensions: 1505 x 560 x 1790 (h) mm
Test results:

Element tested: shelf

Dimensions of the shelf: 1455 x 175 x 12 h mm
Maximum admissible load declared: 5 kg

Load on the shelf (2 x allowable load) kg	Load application time	Remarks
10	24 h	none

Element tested: shelf

Dimensions of the shelf: 1455 x 175 x 12 h mm
Maximum admissible load declared: 5 kg

Load on the shelf (2 x allowable load) kg	Load application time	Remarks
10	24 h	none

Element tested: nr 2 hanging shelves

Dimensions of the shelf: 1455 x 175 x 12 h mm
Maximum admissible load declared: 1 kg (per each shelf)

Load on the shelf (2 x allowable load) kg	Load application time	Remarks
4	24 h	none

This test report is part of a PDF file digitally signed by Franco Bulian on 14/07/21.

The managing director
Dr. Franco Bulian

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise required by standards and technical specifications or agreed with the customer, any declarations of conformity made by CATAS are based on the comparison between results and reference values, where the confidence intervals of the measures are not taken into account. Unless otherwise stated, sampling is made by the customer; in this case the test results are referred to the sample as received.