narbutas

AURA chair family



QUALITY STANDARD

Task chairs:

- EN 1335-1:2020+A1:2022
- EN 1335-2:2018

Visitor chairs:

• EN 16139:2013

TECHNICAL INFORMATION

Types

• Executive, task and visitor & conference chairs.

Seat

- Depth adjustable (50 mm run range);
- Lower part (inner and outer) made of PP (polypropylene);
- Foam made of polyurethane;
- CFC free (NO chlorofluorocarbon).

Back

- Height adjustable (60 mm run range), 6 locking positions;
- Frame (outer and inner) made of PP (polypropylene);
- Foam made of polyurethane;
- CFC free (NO chlorofluorocarbon);
- Clips fixing system.

Armrests

- Fixed black plastic armrests;
- 2D (two directions) height adjustable armrests. Upper part coated with a PU (polyurethane) pad, soft touch, the lower part is made of black plastic. The top of armrests moving forward or backward;
- 2D (two directions) height adjustable armrests. Upper part coated with a PU (polyurethane) pad, soft touch, the lower part is made of polished aluminium. The top of armrests moving forward or backward;
- 3D (three directions) adjustable black plastic armrests.
- 3D (three directions) adjustable black plastic armrests with polished aluminum lower part.



Rubber free wheel castors for hard floor, Ø65 mm;

PA (polyamide) free wheel castors for soft floor,

Fixed, made of polyurethane and upholstered.

Mechanism

- Synchronized movement of seat and back;
- 5 locking positions of the backrest;
- Tension adjustment with handwheel (task and executive chairs).

Gas lift


- Chromed or black colour; •
- 105 mm run range.

Bases


- Five-star polished aluminium base. External 700 mm; •
- Five-star black PA (polyamide) with fiberglass base. External 680 mm;
- Four-legged reinforced steel chromed frame, Ø25 mm; .
- Four legged with 4 wheels reinforced steel chromed frame, Ø25 mm; .
- Reinforced steel chromed cantilever frame, Ø25 mm; .
- 4-star steel chromed frame with glides. •


RANGE

Executive



Visitor & conference






00

.

55

. 460



*Height approved during certification.

Optional





2D armrests, lower

part - plastic



2D armrests, lower part - aluminium



3D armrests, lower part - plastic



125-530

00

3D armrests, lower part - aluminium

Castors

Ø65 mm.

Headrest

•

•

•

Task

460

500

680 / 700

65