

SEPA' ROLLS

SPECIFICATION

Range: SEPA' ROLLS Design: Sezgin Aksu

Freestanding "Snowsound Fiber Technology" sound-absorbing element.

Fabric description:

"Snowsound Fiber 3 Melange" sound absorbing fabric made entirely of polyester, equipped with a zipper at the end that allows its removal.

The fabric has a Class1 fire reaction (Italian standard) and Euroclass B-s1, d0.

The fabric is **Greenguard Gold certified**, which certifies its low VOC emission and its contribution to the quality of the indoor environment.


The fabric is **100% recyclable** and has no detectable formaldehyde content according to UNI EN 717-2. It doesn't contain felt or other organic materials (hard to recycle).

Fabric Metrature: 3,9 m²

Structure description:

Structure consisting of two uprights, made of chromed steel tube ø 28 mm, at which two crossbars are screwed (top and bottom), also made in tubular steel ø 25 mm. One upright ends at the bottom with a foot technopolymer support, the other is welded to a chromed tubular steel base ø 28 mm, equipped at both ends with one-way technopolymer wheels.

Dimensions:









Available colors:









SPECIFICATION

Range: **SEPA'** Design: **Sezgin Aksu**

Freestanding "Snowsound Fiber Technology" sound-absorbing element.

Fabric description:

"Snowsound Fiber 3 Melange" sound absorbing fabric made entirely of polyester, equipped with a zipper at the end that allows its removal.

The fabric has a Class1 fire reaction (Italian standard) and Euroclass B-s1, d0.

The fabric is **Greenguard Gold certified**, which certifies its low VOC emission and its contribution to the quality of the indoor environment.


The fabric is **100% recyclable** and has no detectable formaldehyde content according to UNI EN 717-2. It doesn't contain felt or other organic materials (hard to recycle).

Fabric Metrature: 4,9 m²

Structure description:

Structure consisting of two uprights, made of chromed steel tube ø 28 mm, at which two crossbars are screwed (top and bottom), also made in tubular steel ø 25 mm. The bases, made of 5 mm thick, epoxy powder coated steel sheet are fixed to the uprights by 3 M6x20 screws.

Dimensions:





Available colors:



